





Racing Success Starts Here!

Powered by a liquid-cooled, SCEM-plated 84.7cm³ engine and an agile chassis featuring fully adjustable inverted front forks and rear shock absorber, the RM85 - with 17-inch front / 14-inch rear tires, or the RM85L - with 19-inch front / 16-inch rear tires – both got what it takes to fuel the newest memories of future champions.









Textured surface seat

84.7cm3 2-stroke engine

PHOTO: RM85 Champion Yellow No.2 (YU1)

- 84.7cm³, 2-stroke, liquid-cooled, crankcase reed-valve engine with bore and stroke of 48.0mm x 46.8mm. The cylinder features Suzuki Composite Electrochemical Material (SCEM) for durability, weight reduction and effective heat transfer to get superior class performance.
- Exhaust valves made of aluminum to match well the expansion rate of the cylinder itself improve sealing.
- The exhaust valve governor and actuator with good throttle response and tractability.
- Digital CDI map offers the suitable engine performance
- Smooth shifting 6-speed transmission features a fully worked-out shift mechanism, including strong shift-drum detent spring and needle bearing on the left side of the shift

- Knurled shift-pedal tip delivers excellent grip and shift feel.
- Tubular steel frame and aluminum swingarm with thick wall for performance on the track, especially in the corners.
- SHOWA inverted front forks are completely adjustable for rider weight, style and ability. A large-diameter fully-adjustable rear shock absorber produces plush feel with strong bottoming resistance. The front forks offer 275mm (10.8 in) and the rear 277mm (10.9 in) of wheel travels.
- 2-piston caliper front brake with 220mm (8.7 in) large-diameter disc and rear brake with 200mm (7.9 in) disc provide excellent braking performance.
- Light small-diameter front and rear brake hose. brake hose is routed behind the fork leg, eliminating the need for a brake hose cover and reducing weight.

- Rigid rear brake caliper with reliable braking performance, long pad life and easy maintenance.
- Plastic rear brake caliper guard reduces the possibility of deformation and saving weight as well.
- \blacksquare A forged aluminum-alloy rear brake pedal gives the rider accurate braking feel.
- Footpegs are made of cast chrome-molybdenum steel, instead of stamped steel, making them more durable with
- A long clutch lever makes it easy to accurately locate and work the engagement point during starts and when clutching off at corners.
- Each side of the seat has textured surface for better knee gripping.

Specifications							
Engine Type			2-stroke, 1-cylinder, liquid-cooled				
Engine Displacement				84.7 cm ³ (5.2 cu. in)			
Bore x Stroke				48.0 mm x 46.8 mm			
Compression Ratio			9.5	9.5 / 10.9 : 1 (Ex valve open / Ex valve close			
Transmission			6-s	6-speed constant mesh			
Overall Length	RM	85 / 85L	180	5 / 1895 mm	(71.1 / 74.6	in)	
Overall Width				735 mm	(28.9 in)		
Overall Height	RM	85 / 85L	110	0 / 1165 mm	(43.3 / 45.9	in)	
Wheelbase	RM	85 / 85L	124	0 / 1280 mm	(48.8 / 50.4	in)	
Ground Clearance RM85 / 85L			32	5 / 355 mm	(12.8 / 14.0	in)	
Seat Height	RM	85 / 85L	85	0 / 875 mm	(33.5 / 34.4	in)	
Curb Mass	RM	85 / 85L	7	3 / 74 kg	(161 / 163 II	bs)	
Suspension	Front		Tele	Telescopic, pneumatic/coil spring,			
			oil	oil damped			
	Rear		Link	Link type, coil spring, oil damped			
Brakes	Front		Disc	Disc			
	Rear		Disc	Disc			
Tires	Front	RM85	70/	70/100-17 40M			
		RM85L	70/	100-19 42M			
	Rear	RM85	90/	100-14 49M			
		RM85L	90/	100-16 52M			
Ignition Type			Elec	Electronic ignition (CDI)			
Fuel Tank Capacity			5.0	5.0 L (1.3 US gal)			

Color

Photo: RM85



Champion Yellow No.2 (YU1)

*The RM85 and RM85L are for closed-course competition use and related practices only. Always supervise young riders. Specifications, appearance, colors (including body color), equipment, materials and other aspects of the "SUZUKI" products shown in this catalogue are subject to change by Suzuki at any time without notice, and they may vary depending on local conditions or requirements. Some models are not available in some regions. Each model may be discontinued without notice. Please inquire at your local dealer for details of any such changes.

Always wear a helmet, eye protection and protective clothing. Enjoy riding safely. Read your Owner's Manual carefully.

Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN RM85/L L5 Leaflet 99999-A2201-151 MAY'14 SUZUKI MOTOR CORPORATION

300 Takatsuka-cho, Minami-ku, Hamamatsu City, Japan 432-8611

www.globalsuzuki.com

