



Way of Life!

SUZUKI
KINGQUAD 750AXi / POWER STEERING
4x4



Photo : KINGQUAD 750AXi 4x4 Power Steering

Mighty King Of The KINGQUAD Family

SUZUKI's premium utility/sport ATV, powered by a fuel-injected 4-valve 722cm³ engine tuned to deliver a mighty low-to-mid range torque. The machine for those who need the best of every feature. Available with electric power steering offering steering assistance when the rider needs it or the ground demands it.

SUZUKI
KINGQUAD 750AXI 4x4 / POWER STEERING



Photo : KINGQUAD 750AXI 4x4

Terra Green (YLG)

- Compact and lightweight electric power steering delivers lighter steering in a variety of conditions to reduce rider fatigue. It is positioned high on the vehicle to avoid water and debris. (KINGQUAD 750AXI 4x4 Power Steering only)

- 722cm³ liquid-cooled DOHC 4-valve fuel-injected engine is tuned to deliver a mighty low-to-mid range torque along with a powerful high-rpm output.

- Fuel injection improves throttle response and fuel efficiency, while delivering power consistently and improving starting.

- The rubber-mounted engine uses two balancer shafts to keep the powerful ride smooth.

- Air filter has both paper (for superior filtration) and foam (easily cleaned and re-used) elements for better durability and less maintenance.

- Efficient and functional fully automatic QuadMatic Continuously Variable Transmission (CVT), using a durable V-belt and centrifugal clutch.

- An advanced engine-braking system helps the transmission control speed on descents and when pulling a load.

- Torque-sensing front differential with three modes - 2WD, 4WD or differential-locked 4WD - easily selected with a handlebar-mounted button.

- Fully independent suspension system with adjustable shock absorbers. Shock absorbers at all four corners are adjustable for five different preload settings and can be easily adjusted out on the trail.

- Front dual hydraulic disc brakes and rear sealed oil-bathed multi-disc braking system deliver strong and consistent stopping performance.

- Gate-style drive mode selector lever lets the rider easily and securely select between low and high range, or the neutral or reverse settings.

- Suzuki's exclusive T-shaped seat, designed for all-day comfort and easier body-weight transition.

- Fuel tank positioned below the seat helps keep the machine's weight center low. The tank's ratcheting gas cap is easy to tighten.

- A handy storage compartment is mounted on the right-side front fender.

- Handlebar-mounted auxiliary headlight gives focused lighting in the direction of intended travel, and can be switched off independently.

- LCD instrumentation includes speedometer, odometer, twin tripmeters, clock, hour meter, gear indicator, fuel gauge, and drive mode readouts.



Drive-mode system



Full floorboards with drain holes



12V DC power outlet

Specifications

Engine Type	4-stroke, 1-cylinder, liquid-cooled, DOHC
Engine Displacement	722 cm ³ (44.1 cu. in)
Bore x Stroke	104.0 mm x 85.0 mm
Compression Ratio	9.9 : 1
Transmission	CVT, 2-speed forward with reverse
Overall Length	LT-A750X / XP 2135 mm (84.1 in) / 2165 mm (85.2 in)
Overall Width	LT-A750X / XP 1250 mm (49.2 in) / 1250 mm (49.2 in)
Overall Height	LT-A750X / XP 1245 mm (49.0 in) / 1285 mm (50.6 in)
Wheelbase	LT-A750X / XP 1280 mm (50.4 in) / 1285 mm (50.6 in)
Ground Clearance	LT-A750X / XP 270 mm (10.6 in) / 260 mm (10.2 in)
Seat Height	LT-A750X / XP 880 mm (34.6 in) / 920 mm (36.2 in)
Curb Mass	LT-A750X / XP 304 kg (670 lbs) / 307 kg (677 lbs)
Suspension	Front Independent, double wishbone, coil spring, oil-damped Rear Independent, double wishbone, coil spring, oil-damped
Brakes	Front Disc, twin Rear Sealed oil-bathed multi-disc
Tires	Front AT25x8-12 ^{☆☆} , tubeless Rear AT25x10-12 ^{☆☆} , tubeless
Ignition Type	Electronic ignition (CDI)
Fuel Tank Capacity	17.5 L (4.6 US gal)

Colors



Flame Red (YT9)
Photo : LT-A750XP



Solid Black No.2 (YLZ)
Photo : LT-A750XP



True Timber XD3 (PHW)
Photo : LT-A750XPZ



Metallic Mat Royal Gray (PNB)
Photo : LT-A750XPZ

Specifications, appearance, colors (including body color), equipment, materials and other aspects of the "SUZUKI" products shown in this catalogue are subject to change by Suzuki at any time without notice, and they may vary depending on local conditions or requirements. Some models are not available in some regions. Each model may be discontinued without notice. Please inquire at your local dealer for details of any such changes.

■ Always wear a helmet, eye protection and protective clothing. ■ Enjoy riding safely.
■ Read your Owner's Manual carefully. ■ Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN KINGQUAD 750AXI 4x4/Power Steering (LT-A750X/XZ/XP/XPZ) L5 Leaflet 99999-A3104-151 MAY'14

SUZUKI MOTOR CORPORATION

300 Takatsuka-cho, Minami-ku, Hamamatsu City, JAPAN 432-8611

www.globalsuzuki.com

ATV SAFETY INFORMATION

The Suzuki KINGQUAD 750AXI 4x4/Power Steering may be used only by those aged 16 and older. ATVs can be hazardous to operate. For your safety, always wear a helmet, eye protection and protective clothing. Always avoid paved surfaces. Never ride on public roads. Never carry passengers or engage in stunt riding. Riding and alcohol or other drugs don't mix. Avoid excessive speed. Be extra careful on difficult terrain. Read your Owner's Manual carefully.

