





The Top Performer In Its Class

A lightweight chassis featuring a compact wheelbase and race-developed suspension. A compact, powerful 4-cylinder engine delivering a real-world demonstration of advanced race-proven technology. The GSX-R600 - designed to be The Top Performer in its class, a total package designed to Own The Racetrack.





Metallic Triton Blue / Pearl Glacier White (AGQ)

- 599cm³ 4-cylinder engine with a race-proven oversquare bore/stroke ratio for an efficient, high-revving design.
- The engine employs shot-peened conrods, chrome-nitride-coated upper compression and oil control rings, and pentagonal ventilation holes.
- Lightweight and durable forged pistons designed using Finite Element Method (FEM) and fatigue analysis technology used for MotoGP racing engines.
- Camshaft profiles for an aggressive valve-lift curve are developed using proven MotoGP racing engine technology its first use on a production Suzuki.
- Suzuki Dual Throttle Valve (SDTV) fuel injection uses fine-spray 8-hole injectors for improved fuel atomization, which contributes to more complete computation
- Advanced, MotoGP-developed transistorized ignition control circuit helps maintain more precise spark timing across the range of engine temperature.
- Suzuki Drive Mode Selector (S-DMS) offers push-button selection of two racing-developed engine control maps to suit road conditions and personal tastes

- 4-into-1 stainless-steel exhaust system with a titanium muffler carries a Suzuki Exhaust Tuning (SET) valve maximizing torque and improving throttle response, especially in the low-to-mid rpm range.
- Race-proven back-torque-limiting clutch contributes to smoother downshifting and corner entry.
- Lightweight and compact twin-spar aluminum cradle frame is made of five cast sections and cast swingarm.
- Race-developed, lightweight Showa Big Piston front Forks (BPF) deliver superb feedback and consistent performance.
- Single Showa rear shock absorber features externally adjustable rebound and compression damping, along with adjustable ride height.
- Electronically controlled steering damper provides lighter steering at slower speeds and more damping force at racetrack and highway speeds.
- Front brakes with fully floating 310mm discs and radial-mount, four-piston Brembo monoblock calipers.



3-Way adjustable footpeg



Front brake system with Brembo



Suzuki Drive Mode Selector (S-DMS)

- 3-way adjustable footpegs, adjustable shift lever and short fuel tank help compose a comfortable riding position.
- Compact, lightweight instrument cluster with a built-in lap timer/stopwatch and programmable engine rpm indicators.
- Small, simple and lightweight bodywork composes an exciting, aerodynamic styling.
- Analog tachometer. LCD readouts include speedometer, odometer, dual trip meter, reserve trip meter, clock, coolant temperature/oil pressure indicator, S-DMS and gear position indicators.
- Suzuki Advanced Immobilizer System (SAIS) is standard in selected markets. (For European and Australian specs. only.)

Engine Type 4-stroke, 4-cylinder, liquid-cooled, DOHC Engine Displacement 599 cm³ (36.5 cu. in) Bore x Stroke 67.0 mm x 42.5 mm (2.6 in x 1.7 in) Compression Ratio 12.9 : 1 Transmission 6-speed constant mesh Overall Length 2030 mm (79.9 in) Overall Width 710 mm (28.0 in) Overall Height 1135 mm (44.7 in) Wheelbase 1385 mm (54.5 in) Ground Clearance 130 mm (5.1 in) Seat Height 810 mm (31.9 in) Curb mass 187 kg (412 lbs) Suspension Front Inverted telescopic, coil spring, oil damped Rear Link type, coil spring, oil damped Brakes Front Rear Disc Tires Front Rear 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)		Speci	itications
Bore x Stroke 67.0 mm x 42.5 mm (2.6 in x 1.7 in) Compression Ratio 12.9 : 1 Transmission 6-speed constant mesh Overall Length 2030 mm (79.9 in) Overall Width 710 mm (28.0 in) Overall Height 1135 mm (44.7 in) Wheelbase 1385 mm (54.5 in) Ground Clearance 130 mm (5.1 in) Seat Height 810 mm (31.9 in) Curb mass 187 kg (412 lbs) Suspension Front Inverted telescopic, coil spring, oil damped Rear Link type, coil spring, oil damped Brakes Front Disc, twin Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Engine Type		, , , , , ,
Compression Ratio 12.9 : 1 Transmission 6-speed constant mesh Overall Length 2030 mm (79.9 in) Overall Width 710 mm (28.0 in) Overall Height 1135 mm (44.7 in) Wheelbase 1385 mm (54.5 in) Ground Clearance 130 mm (5.1 in) Seat Height 810 mm (31.9 in) Curb mass 187 kg (412 lbs) Suspension Front Inverted telescopic, coil spring, oil damped Rear Link type, coil spring, oil damped Brakes Front Disc, twin Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Engine Displacement		599 cm ³ (36.5 cu. in)
Transmission 6-speed constant mesh Overall Length 2030 mm (79.9 in) Overall Width 710 mm (28.0 in) Overall Height 1135 mm (44.7 in) Wheelbase 1385 mm (54.5 in) Ground Clearance 130 mm (5.1 in) Seat Height 810 mm (31.9 in) Curb mass 187 kg (412 lbs) Suspension Front Inverted telescopic, coil spring, oil damped Rear Link type, coil spring, oil damped Brakes Front Disc, twin Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Bore x Stroke		67.0 mm x 42.5 mm (2.6 in x 1.7 in)
Overall Length 2030 mm (79.9 in) Overall Width 710 mm (28.0 in) Overall Height 1135 mm (44.7 in) Wheelbase 1385 mm (54.5 in) Ground Clearance 130 mm (5.1 in) Seat Height 810 mm (31.9 in) Curb mass 187 kg (412 lbs) Suspension Front Inverted telescopic, coil spring, oil damped Rear Link type, coil spring, oil damped Brakes Front Disc, twin Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Compression Ratio		12.9:1
Overall Width 710 mm (28.0 in) Overall Height 1135 mm (44.7 in) Wheelbase 1385 mm (54.5 in) Ground Clearance 130 mm (5.1 in) Seat Height 810 mm (31.9 in) Curb mass 187 kg (412 lbs) Suspension Front Inverted telescopic, coil spring, oil damped Rear Link type, coil spring, oil damped Brakes Front Disc, twin Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Transmission		6-speed constant mesh
Overall Height 1135 mm (44.7 in) Wheelbase 1385 mm (54.5 in) Ground Clearance 130 mm (5.1 in) Seat Height 810 mm (31.9 in) Curb mass 187 kg (412 lbs) Suspension Front Inverted telescopic, coil spring, oil damped Rear Link type, coil spring, oil damped Brakes Front Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Overall Length		2030 mm (79.9 in)
Wheelbase 1385 mm (54.5 in) Ground Clearance 130 mm (5.1 in) Seat Height 810 mm (31.9 in) Curb mass 187 kg (412 lbs) Suspension Front Inverted telescopic, coil spring, oil damped Rear Link type, coil spring, oil damped Brakes Front Disc, twin Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Overall Width		710 mm (28.0 in)
Ground Clearance 130 mm (5.1 in) Seat Height 810 mm (31.9 in) Curb mass 187 kg (412 lbs) Suspension Front Inverted telescopic, coil spring, oil damped Rear Link type, coil spring, oil damped Brakes Front Disc, twin Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Overall Height		1135 mm (44.7 in)
Seat Height 810 mm (31.9 in) Curb mass 187 kg (412 lbs) Suspension Front Inverted telescopic, coil spring, oil damped Rear Link type, coil spring, oil damped Brakes Front Disc, twin Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Wheelbase		1385 mm (54.5 in)
Curb mass Suspension Front Inverted telescopic, coil spring, oil damped Rear Link type, coil spring, oil damped Brakes Front Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Ground Clearance		130 mm (5.1 in)
Suspension Front Inverted telescopic, coil spring, oil damped Rear Link type, coil spring, oil damped Brakes Front Disc, twin Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Electronic ignition (Transistorized)	Seat Height		810 mm (31.9 in)
Rear Link type, coil spring, oil damped Brakes Front Disc, twin Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Curb mass		187 kg (412 lbs)
Brakes Front Disc, twin Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Suspension	Front	
Rear Disc Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)		Rear	Link type, coil spring, oil damped
Tires Front 120/70ZR17M/C (58W), tubeless Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)	Brakes	Front	Disc, twin
Rear 180/55ZR17M/C (73W), tubeless Ignition Type Electronic ignition (Transistorized)		Rear	Disc
Ignition Type Electronic ignition (Transistorized)	Tires	Front	120/70ZR17M/C (58W), tubeless
		Rear	180/55ZR17M/C (73W), tubeless
,	Ignition Type		Electronic ignition (Transistorized)
Fuel Tank 17.0 L (4.5 US gal)	Fuel Tank		17.0 L (4.5 US gal)

Spacifications



Colors

Pearl Bracing White / Glass Sparkle Black (AR5)

Specifications, appearance, colors (including body color), equipment, materials and other aspects of the "SUZUKI" products shown in this catalogue are subject to change by Suzuki at any time without notice, and they may vary depending on local conditions or requirements. Some models are not available in some regions. Each model may be discontinued without notice. Please inquire at your local dealer for details of any such changes.

Always wear a helmet, eye protection and protective clothing.

Read your Owner's Manual carefully.

■ Enjoy riding safely.
■ Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN GSX-R600 L4 Leaflet 99999-A0111-141 JUL.'13

SUZUKI MOTOR CORPORATION
300 Takatsuka-cho, Minami-ku, Hamamatsu City, JAPAN 432-8611

www.globalsuzuki.com

