



SUZUKI

Way of Life!



**C1500/T**



# CHOOSE YOUR BOULEVARD

Weekend wandering with your motorcycle friends. Long-distance adventure, just you and the road. Or simply your best ride to work. The INTRUDER C1500/T motorcycle complete your cruiser experience. Choose your Boulevard.




**C 1500/T**



Photo : VL1500BT

Glass Sparkle Black (YVB)



1462 cm<sup>3</sup> liquid-cooled V-Twin engine



Hard side cases (VL1500T/BT only)



Windscreen (VL1500T/BT only)

- Liquid-cooled, 1462cm<sup>3</sup> long-stroke V-twin engine delivers the most power and torque in the class\*. Outstanding low-to-mid range output means smooth acceleration and comfortable long-range cruising characteristics. \*1000cm<sup>3</sup> to 1600cm<sup>3</sup> cruiser class

- Suzuki's advanced fuel-injection system with Suzuki Dual Throttle Valve (SDTV) induction delivers seamless throttle response while boosting fuel efficiency and torque delivery.

- The four-valve cylinder head with overhead camshafts and dual spark plugs increases combustion efficiency to help ensure seamless throttle response, gutsy low-to-mid range output, better fuel efficiency, and reduced emissions.

- To maximize air induction for best power and torque, the INTRUDER C1500/T features a unique system that uses three separate air-cleaner boxes feeding the engine. This air induction system increases engine output without sacrificing style or fuel tank capacity.

- The Suzuki Clutch Assist System (SCAS) reduces the force needed to pull in the clutch lever, so clutch operation remains light. The clutch features back torque limiting clutch system, contributing to smooth down shift operation.

- The appeal of classic styling is married with the benefits of modern performance, with the steel-tube frame comfortably carrying the rider and confidently housing the powerful engine.

- Both rider and passenger seats are made for long-range comfort and top-notch control. They allow freedom of movement, accommodate riders of different sizes, and are well cushioned.

- The design of the link-type rear suspension maintains classic hard-tail look, while keeping the ride low and producing a smooth, ground-hugging ride.

- Convenient touring-friendly features include the footboards, 18-litre (4.8-gallon) fuel tank, shaft drive, lockable storage, and easy-to-use helmet holder.

- The factory built hard side cases are made of durable, impact-resistant PP plastic under stylish covers custom-matched to the seats. They're designed as part of the bike, not as luggage add-ons. (INTRUDER C1500T only)

- The windscreen with subtle styling that is designed to provide ample wind protection at freeway speeds and to minimize wind buffeting. (INTRUDER C1500T only)

- The multi-function instrument includes a convenient gear-position indicator and a fuel gauge, along with a clock and a trip meter, plus indicator lights for low fuel, turn signals and more.

- VL1500B and VL1500BT feature a black engine and pipes, all-black wheels and fully inked over details. When you ride one, you are the king of the right.

Specifications, appearances, equipments, colors, materials and other items of "SUZUKI" products shown on this catalogue are subject to change by manufacturers at any time without notice and they may vary depending on local conditions or requirements. Some models are not available in some territories. Each model might be discontinued without notice. Please inquire at your local dealer for details of any such changes. Actual body color might differ from the colors in this catalogue.

■ Always wear a helmet, eye protection and protective clothing. ■ Enjoy riding safely.  
 ■ Read your Owner's Manual carefully. ■ Never ride under the influence of alcohol or other drugs.

PRINTED IN JAPAN INTRUDER C1500/T (VL1500/B/T/BT) Leaflet L4 99999-A0019-141 SEP'13

**SUZUKI MOTOR CORPORATION**

300 Takatsuka-cho, Minami-ku, Hamamatsu City, JAPAN 432-8611

www.globalsuzuki.com

"INTRUDER C1500" is the model name mainly used for European market.

## Specifications

Engine Type	4-stroke, 2-cylinder, liquid-cooled, SOHC, 54° V-Twin	
Engine Displacement	1462 cm <sup>3</sup> (89.2 cu. in.)	
Bore x Stroke	96.0 mm x 101.0 mm	
Compression Ratio	9.5 : 1	
Transmission	5-speed constant mesh	
Overall Length	2570 mm (101.2 in.)	
Overall Width	990 mm (39.0 in.)	
Overall Height	VL1500/B	1135 mm (44.7 in.)
	VL1500T/BT	1440 mm (56.7 in.)
Wheelbase	1675 mm (65.9 in.)	
Ground Clearance	140 mm ( 5.5 in.)	
Seat Height	720 mm (28.3 in.)	
Curb Mass	VL1500/B	344 kg (758 lbs)
	VL1500T/BT	363 kg (800 lbs)
Suspension	Front	Inverted telescopic, coil spring, oil damped
	Rear	Link type, coil spring, oil damped
Brakes	Front	Disc
	Rear	Disc
Tires	Front	130/80R 17M/C (65H), tubeless
	Rear	200/60R 16M/C (79H), tubeless
Ignition Type	Electronic ignition (Transistorized)	
Fuel Tank Capacity	18.0 L (4.8 US gal)	

## Colors



Candy Indy Blue (YKZ)  
Photo : VL1500



Glass Sparkle Black (YVB)  
Photo : VL1500B



Metallic Fox Orange /  
Glass Midnight Brown (AW4)  
Photo : VL1500T



Solid Special White No.2 /  
Solid Iron Gray (HYB)  
Photo : VL1500T

